AMENDMENTS TO THE CLAIMS:

Please cancel claims 20 and 22, without prejudice. Kindly amend claims 1-10, 12-16, 21, and 23-26, as shown below.

This listing of claims will replace all prior versions and listings of claims in the Application:

Claim 1 (currently amended): Micro-hotplate device with integrated chemical sensor, which comprises:

- a) a support substrate;
- b) a supported membrane, supported by and attached to said support substrate, extending over a well in said support substrate;
- c) an island attached to said membrane so as to be and electrically and thermally isolated from said substrate, said island consisting at least partly comprised of a semiconducting material;
- d) at least one or several heating elements element integrated in said island;
- e) <u>at least</u> one or several temperature-sensing elements element integrated in said island;
- f) at least one or several active microelectronic devices device integrated in said island, where wherein said at least one of said at least one active microelectronic devices device is a chemical sensor whose chemically active layer is exposed to the ambient and which is based on a field-effect detection mechanism.

HAYES SOLOWAY P.C.

130 W. CUSHING ST. TUCSON, AZ 85701 TEL. 520.882.7623 FAX. 520.882.7643

Claim 2 (currently amended): A micro-hotplate device according to claim 1, wherein <u>said</u> at least one heating element <u>consists of comprises</u> a heating transistor.

Claim 3 (currently amended): A micro-hotplate device according to claim 1, wherein <u>said</u> at least one heating element <u>eonsists of comprises</u> a heating resistor.

Claim 4 (currently amended): A micro-hotplate device according to claim 1, wherein <u>said</u> at least one temperature-sensing element [[is]] <u>comprises</u> a temperature-sensitive resistor.

Claim 5 (currently amended): A micro-hotplate device according to claim 1, wherein <u>said</u> at least one temperature-sensing element [[is]] <u>comprises</u> a temperature-sensitive diode.

Claim 6 (currently amended): A micro-hotplate device according to claim 1, wherein said membrane eonsists of comprises at least one or several insulator layers layer.

Claim 7 (currently amended): A micro-hotplate device according to claim 6, wherein said at least one insulator [[is]] layer is comprised of silicon nitride.

Claim 8 (currently amended): A micro-hotplate device according to claim 6, comprising a plurality of insulator layers, wherein electrically conducting leads to the active microelectronic devices on the island have been are placed between different said insulator layers.

Claim 9 (currently amended): A micro-hotplate device according to claim 1, wherein the semiconducting material in the island [[is]] comprises silicon.

Claim 10 (currently amended): A micro-hotplate device according to claim 1, wherein the semiconducting material in the island [[is]] comprises silicon carbide.

Claim 11 (previously presented): A micro-hotplate device according to claim 1, wherein the support substrate and the island are made of the same material.

HAYES SOLOWAY P.C. 130 W. CUSHING ST. TUCSON, AZ 85701 TEL. 520.882.7623 FAX. 520.882.7643

Claim 12 (currently amended): A method for the fabrication of a micro-hotplate device according to claim1 as claimed in claim 1, which comprises characterized in the use of a combination of masking steps and etching steps to define [[the]] a geometry of the device.

Claim 13 (currently amended): A method according to claim 12, characterized in the use said etching steps comprise a plurality of consecutive backside etching steps comprising:

- a) depositing [[the]] <u>a</u> supporting membrane over [[the]] <u>a</u> silicon substrate;
- b) <u>a first one</u> etching step is used to define [[the]] <u>a</u> thickness of the island by etching away [[the]] <u>a</u> region surrounding the island to a certain wanted depth, equal to the wanted <u>a target</u> thickness of the island; <u>and</u>
- c) <u>a second another</u> etching step is used to etch for etching the island and surrounding region until the island is isolated from the support substrate.

Claim 14 (currently amended): A method according to claim 12, characterized in the use of wherein a silicon-on-insulator wafer is used as the substrate whereby [[the]] a buried insulator layer in said silicon-on-insulator wafer is used as an etch stop to define [[the]] a thickness of [[the]] an island of the device, resulting in a silicon island with an insulator layer on its backside.

Claim 15 (currently amended): A method according to claim 14, characterized in the use of and further comprising the following steps:

- a) etching away from [[the]] <u>a</u> front side of the device [[the]] <u>a</u> region surrounding the island down to the buried insulator layer; <u>and</u>
- b) etching away from [[the]] \underline{a} back side of the device [[the]] silicon in [[the]] \underline{a} region below the island and [[the]] \underline{a} region surrounding the island until the buried

HAYES SOLOWAY P.C. 130 W. CUSHING ST. TUCSON, AZ 85701 TEL. 520.882.7623 FAX. 520.882.7643

insulator layer on the island is exposed and the island is attached to the support by the insulator layer.

Claim 16 (currently amended): A method according to claim 14, characterized by and further comprising the following steps:

- a) oxidizing the silicon layer on [[the]] <u>a</u> front side of the device down to the buried insulator layer, except for [[the]] <u>a</u> region where the island should be;
- b) etching away from [[the]] <u>a</u> front side of the device [[the]] oxide in [[the]] <u>a</u> region surrounding the island until the underlying silicon substrate is exposed; <u>and</u> [[c]]<u>c</u>) etching away from [[the]] <u>a</u> back side of the device [[the]] silicon in [[the]] <u>a</u> region below the island until [[the]] <u>a</u> buried insulator layer on the island is exposed and the island is attached to the support by the remaining part of the insulator layer.

Claim 17 (previously presented): A method according to claim 12, wherein at least one of said etching steps is an anisotropic potassium hydroxide etching step.

Claim 18 (previously presented): A method according to claim 12, wherein at least one of said etching steps is an anisotropic tetramethyl ammonium hydroxide etching step.

Claim 19 (previously presented):) A method according to claim 12, wherein at least one of said etching steps is a deep reactive ion etching step.

Claim 20 (cancelled)

Claim 21 (currently amended): A micro-hotplate device according to claim 20, wherein one or several field-effect chemical sensors are combined with one or several and further comprising at least one chemical sensors sensor that utilize utilizes a detection mechanism different from [[the]] a field-effect field-effect detection mechanism.

HAYES SOLOWAY P.C. 130 W. CUSHING ST. TUCSON, AZ 85701

TUCSON, AZ 85701 TEL. 520.882.7623 FAX. 520.882.7643

Claim 22 (cancelled)

Claim 23 (currently amended): A micro-hotplate device according to claim 21, wherein one or several comprising at least one field-effect detection gas sensors are sensor combined with at least one or several gas sensors sensor that utilize utilizes resistance changes change as a detection mechanism.

Claim 24 (currently amended): A micro-hotplate device according to claim 23, wherein <u>said</u> at least one of the gas sensor that <u>utilize</u> <u>utilizes</u> resistance <u>changes</u> as <u>a</u> detection mechanism is made of a semiconducting metal oxide.

Claim 25 (currently amended): A micro-hotplate device according to claim 23, wherein <u>said</u> at least one of the gas sensor that <u>utilize</u> <u>utilizes</u> resistance changes change as a detection mechanism is made of a polymer.

Claim 26 (currently amended): A micro-hotplate device according to claim 1, wherein the support substrate contains comprises an array of several islands.

HAYES SOLOWAY P.C.

130 W. CUSHING ST. TUCSON, AZ 85701 TEL. 520.882.7623 FAX. 520.882.7643

175 CANAL STREET MANCHESTER, NH 03101 TEL. 603.668.1400 FAX. 603.668.8567

10